



UTILITY MANUFACTURING CO., INC.
700 MAIN STREET, WESTBURY, NY 11590
(516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

98656

DRY LIME SOLV SCALE DISSOLVER

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure, or Accident - Call **INFOTRAC** - Day or Night: 1-800-535-5053
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) **IMPORTANT:** Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers and users of this product.

PRODUCT IDENTIFICATION

DOT Shipping name: CLEANING COMPOUNDS, NOI CAS NO.: MIXTURE
Chemical Family: INORGANIC ACID UN/NA#: UN2967
DOT Hazard Class: 8 DATE OF ISSUE: 08/04

SECTION I - HAZARDOUS INGREDIENTS/EXPOSURE LIMITS

Hazardous Ingredients:	CAS #	TLV/PEL	AGENCY	TYPE	SARA-313(% Range)
SULFAMIC ACID	5329-14-6	10mg/m3	ACGIH		70-99

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Move person away from exposure and into fresh air. If irritation or redness develops, flush eyes with clean water. For direct contact hold eyelids apart for at least 15 minutes. **Seek medical attention.**
SKIN CONTACT: Remove contaminated shoes and clothing and cleanse affected areas thoroughly by washing with copious amounts of soap and water. If irritation persists **seek medical attention.**
INHALATION: (breathing) Not expected to be a hazard under normal operating conditions.
INGESTION: (swallowing) If swallowed, **seek emergency medical attention.** Dilute immediately by drinking large quantities of water or milk. Do not give anything by mouth to an unconscious person.

SECTION III - HEALTH HAZARDS / ROUTES OF ENTRY

EYE CONTACT: Corrosive. May cause corneal and conjunctival edema, corneal opacity, and corneal destruction accompanied by pain, lacrimation, and blurred vision.
SKIN CONTACT: Continuous contact with this material will cause skin burns and severe pain. Chemical itself is an irritant or sensitizer.
SKIN ABSORPTION: Symptoms of toxicity are anticipated by this route.
INHALATION: (breathing) Inhalation of fumes or dust may cause choking, headache, dizziness, weakness, hypotension and delayed pulmonary edema with chest tightness, apnea, and cyanosis.
INGESTION: (swallowing) Ingestion of large quantities may cause the following: Irritation of digestive tract, signs of nervous system depression, such as headache, drowsiness, dizziness, loss of coordination, fatigue, and nausea.

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION: If current ventilation practices are not adequate to maintain airborne concentrations below established exposure limits (see section I), additional ventilation or exhaust systems may be required.
RESPIRATORY PROTECTION: The use of respiratory protection is advised when concentrates exceed the established exposure limits (see Section I). Depending on the airborne concentration use a respirator or gas mask with appropriate cartridges or canisters (NIOSH approved) or supplied air.
PROTECTIVE GLOVES: The use of gloves impermeable to the specific material handled is advised to prevent possible irritation.
EYE PROTECTION: Approved eye protection to safeguard against potential eye contact, irritation or injury is required.

SECTION V - REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY: (materials to avoid) This product is incompatible with: Chlorine, Potassium chlorate, Oxidizing agents, strong acids and bases
HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide, oxides of nitrogen and sulfur.
HAZARDOUS POLYMERIZATION: Will not occur



UTILITY MANUFACTURING CO., INC.
700 MAIN STREET, WESTBURY, NY 11590
(516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

DRY LIME SOLV SCALE DISSOLVER

SECTION VI - SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF LEAK OR SPILL: Keep all sources of ignition and hot metal surfaces away from spill/release. Stay upwind and away from spill/release. Isolate hazard area and limit entry to emergency crew only. Stop spill/release if it can be done without risk. Wear appropriate protective equipment including respiratory protection as conditions warrant (see Section IV). Prevent spilled material from entering sewers, storm drains, and natural waterways. Dike far ahead of spill for later recovery and disposal. Spilled material may be absorbed by an appropriate absorbent. Notify fire authorities and appropriate federal, state, and local agencies. If spill/release is excess of EPA reportable quantity, immediately notify the **National Response Center**. Phone **800-424-8802**
WASTE DISPOSAL METHOD: Dispose of product in accordance with local, county, state, and federal regulations.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS: Do not get in eyes, skin or clothing. Do not breathe vapor mist or gas. Keep containers tightly closed, cool, dry, and away from all sources of ignition. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. Use good personal hygiene practices. "Empty" containers contain residue (liquid and/or vapor) and can be dangerous. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: Extinguish with dry chemical, CO₂, water spray or a universal type foam.
FIRE AND EXPLOSION HAZARD: May decompose during contact with flames, heating elements, or in combustion engines releasing irritating gases. Container may explode if heated due to resulting pressure rise.
FIRE FIGHTING PROCEDURES: Wear appropriate protective equipment including respiratory protection as conditions warrant (see Section IV). Stop spill/release if it can be done without risk. Water spray may be useful in minimizing or dispersing vapors and cooling equipment exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes.

SECTION IX - PHYSICAL DATA

APPROXIMATE BOILING POINT (DEG F): >400	PER CENT VOLATILE: NONE
SPECIFIC GRAVITY (68 F): 2.0	FLASH POINT (TCC, DEG F): >200
RELATIVE EVAPORATION RATE (ESTIMATED): <1	PER CENT SOLUBILITY IN WATER: 100
VAPOR PRESSURE @20C mmHg (CALCULATED): <1	

SECTION X - OTHER REGULATORY DATA

SARA	HMIS	
SECTION 302: NONE	Health:	2
SECTION 311 & 312: NONE	Flammability:	1
SECTION 313: See Section II	Reactivity:	1
TSCA	CALIFORNIA PROPOSITION 65	
All components are in full compliance with the TSCA inventory.	NOT LISTED	
RCRA	CERCLA	
NOT REGULATED	NOT REGULATED	

CARCINOGENICITY:

NOT LISTED with NTP or IARC.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformance to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.