

BEST NEW ITEMS

DEC

Want to receive info on our Best New Items each month?

Click Here to subscribe!

Big Larry Work Light #11491

- High-power 400 lumen COB LED work light
- Anodized aircraft-grade aluminum; water and impact-resistant
- Powerful magnetic base
- Top-positioned, ON/OFF button
- Powered by 3 AA batteries (included)

Holster for Big Larry Light #10751





55 Pipe Sealing Cord #99725

Designed for the locking and sealing of metal and plastic pipes and fittings. It needs no cure time and results in an immediate, full pressure seal. The ideal choice for a quick, easy, and reliable seal. The product has approval for gas and potable water and is certified to NSF/ANSI, Standard 61.



- Resistant up to 300°F and 10,000 PSI
- 475' of cord
- General purpose, threaded pipe and fitting sealant
- Non-curing, immediate, full-pressure seal
- For a quick, easy and reliable seal
- WRAS listed, meets BS 6920 for potable water: 0808533
- DVGW/KTW approval for gas and potable water
- Certified to NSF/ANSI, Standard 61

Sharkbite Transition Coupling 1/2 CTS x 1/2 PVC #99153179

3/4" CTS x 3/4" PVC - #99153180

1" CTS x 1" PVC - #99153181

- Connects PVC to copper,
 PEX, CPVC, and PE-RT pipe!
- White collar fits Schedule 40, 80, and 120 PVC pipe. Also fits Schedule 40 and 80 CPVC.
- Instant push-fit connection which means no soldering, clamps, or unions required.
- Fittings certified to 200 PSI and 200°F (93°C)
- Easy to disconnect and reuse
- No Primer or Glue Required
- PVC clip helps you measure where to cut the pipe!

See Section 7 for More Sharkbite fittings.



C-Disconnect Clips

1/2" - #70230

3/4" - #70231

1" - #70232



PVC Depth Gauge & Disconnect Clips

1/2" - #99153185

3/4" - #99153186

1" - #99153187

Ask your sales rep about the Transition Tee's, Slip Couplings, Stops, and elbows.





BEST FEATURED ITEMS



Milwaukee 11 in 1 Screwdriver #99047974

- 5 in. shaft holds up to 9 bits for versatility
- Wire stripper can strip up to 12-gauge wire
- Wire bending hole can bend wire up to 12-gauge
- Includes ECX[™] bit for superior fit in specialty screws
- Includes 6 bits and 3 nut drivers p. 10-3

Over Boot/Shoe Traction #11233 (M), #11236 (L / XL)



Ten times the gripping points as any spike based traction device!

Walk Naturally • Spikeless • Ultralight

MED: 9-11 L / XL: 11.5-13.5

- Every step you take places hundreds of Biting edges in direct contact with the ice beneath your feet
- Made out of an injection molded Thermal plastic elastomer, designed for easy on and off
- The coils are protected against rusting
- Hand-wound to give you 360° of traction on ice and snow
- The outer band conforms to the length and width of your boot or shoe
- High strength horizontal coils provide forward and backward stability
- The vertical coil pattern provides sideto-side stability

p. 6-125

Batteries



#10974 AA Procell

#10998 AAA Procell

#10975 C Procell

#10964 D Procell

#10969 9V Procell

#10968 6V Lithium

#10965 6V Procell Lantern Battery

#10944 AA Lithium (2/pack)

#10995 AAAA Battery (2/pack)

p. 10-77

Did You Know Best Carries?



Milwaukee Thunderbolt **Drill Bits**



- Featuring a thicker core than a standard drill bit, which provides ultimate strength and protects against side-load
- A specially designed parabolic flute form clears, chips and debris fast to keep the bit cool.
- A precision start, 135 Split Point tip, starts on contact to keep the bit from walking.
- Excellent for drilling on curved surfaces and requires less effort to drill. Highly recommended for use with portable drills.

SORRY,


OUT OF SERVICE

p. 10-69

Restroom Stall Block-Aide

#99522619

"Sorry, Out of Service" is a polite and sanitary way to keep people



• Locks the door closed from all patrons until repair can be completed.

• DIMENSIONS: 3" x 1.5" x 4.5"

p. New-5

X-TREME Tape Black 1IN x 10 ft #99847

• 15% more material/thickness than rival brands

- Will not melt up to 260°C (500°F)
- Remains flexible to -50°C (-60°F)
- Tensile strength of 700+PSI
- Insulates to 400 volts/mil
- Resists weathering

p. 6-74





